

Hydraulic Flange Spreaders

Model Number:FM-8

- Capacity:8 Ton
- Minimum required access gap is 1.5 mm.
- Maximum spreading is 25 mm.
- Direct-type, is no need hand pump.
- Use in pairs to provide even force for spreading easily.
- Weight: 5.5 Kg



Model Number:FM-12

- Capacity:12 Ton
- Arc shape is matcher to flange.
- Flange shape design has 4 faces with different thickness layers;
No need safety blocks or step blocks.
- Minimum require access gap is 3 mm,Maximum spreading distance is 34 mm.
- Rotary handle allows pumping at all direction.
- Separate type:needs to operate with hand pump
- Weight: 4.8 Kg



Model Number:FM-16

- Capacity:15 Ton
- Arc shape is matcher to flange.
- Flange shape design has 4 faces with different thickness layers;
No need safety blocks or step blocks.
- Minimum require access gap is 3 mm;Maximum spreading distance is 34 mm.
- Rotary handle allows pumping at all direction.
- Direct-type, is no need hand pump.
- Weight: 5.3 Kg



Hydraulic Flange Spreaders

Model Number:FM-15

- Capacity:15 Ton
- The jaw tips can simply fitting within 6 mm gap.
- Maximum spreading distance is 81 mm.
- Direct-type, is no need hand pump.
2 stepped blocks,1 safety block.
- Accessories:1xcarrying case
- Weight: 7.7 Kg



Model Number:FM-14

- Capacity:14 Ton
- The jaw tips can simply fitting within 6mm gap.
- Maximum spreading distance is 81 mm.
- Separate type needs to operate with hand pump.
- Accessories:1xcarrying case 2 stepped blocks, 1 safety block.
- Weight: 7.71 Kg



Model Number:FM-14H

Flange Spreader Set Includes

- 2 FM-14
- 4 stepped blocks
- 2 safety blocks
- 2 1.8 M hose w/couplers
- 1 manifold needle valve and couplers
- 1 two-stage hand pump
- 1 carrying case



Self Contained Hydraulic Nut Splitters

- Compact and ergonomic design.
- Single-acting, spring return cylinder.
- All nut splitter are supplied with female coupler.
- Replacement blade are readily available.



Model Number	Capacity (Ton)	Hexagon Nut Size (mm)	Bolt Range (mm)	Dimensions(mm)			Weight (kg)	Replacement Blade Model Number
				A	B	D		
ND-1319	5	10-19	M5-M12	40	340	19	2.2	NCB-1319
ND-1924	10	19-24	M12-M16	54	370	25	3.0	NCB-1924
ND-2432	15	24-32	M16-M22	64	403	32	4.7	NCB-2432
ND-3241	20	32-41	M27-M33	75	439	36	6.3	NCB-3241
ND-4150	30	41-50	M33-M39	94	498	45	10.5	NCB-4150

700Bar/10,000psi Separate Hydraulic Nut Splitters

- Compact and ergonomic design, easy to use.
- Unique angled head design.
- Single-acting, spring return cylinder.
- Heavy duty chisels can be reground.
- Applications include service trucks, piping industry, tank cleaning, petrochemical, steel construction, mining, etc.



Model Number	Capacity (Ton)	Oil Capacity (cm ³)	Hexagon Nut Size (mm)	Bolt Range (mm)	Dimensions(mm)			Weight (kg)	Replacement Blade Model Number
					A	B	D		
NS-1319	5	15	10-19	M6-M12	40	170	48	1.2	NCB-1319
NS-1924	10	20	19-24	M12-M16	54	191	62	2.0	NCB-1924
NS-2432	15	60	24-32	M16-M22	64	222	72	3.0	NCB-2432
NS-3241	20	80	32-41	M22-M27	75	244	88	4.4	NCB-3241
NS-4150	35	155	41-50	M27-M33	94	288	105	8.2	NCB-4150
NS-5060	50	240	50-60	M33-M39	106	318	128	11.8	NCB-5060
NS-6075	90	492	60-75	M39-M48	156	393	181	34.1	NCB-6075

